

Aluminium Shutter Care Guide

Aluminium Shutters are made from high-grade aluminium and are low-maintenance and durable. We recommend cleaning your aluminum shutters every six months.

Routine Maintenance

- Wipe over the shutters using a nonabrasive cloth or sponge with warm soapy water. A garden hose can be used applying the same principles.
- Concentrate on the areas where the stainless steel hardware is attached to the shutter.
- Remove any salt residue, tannin stains caused by trees and other marks created.
- On completion of the cleaning process, spray a light film of silicone lubricant to any operational hardware such as the tracking system. Ensure these areas are fully dry prior to this application.
- For shutters installed in premises close to coastal or saltwater environments the following cleaning timeframes are recommended.

Proximity	Cleaning frequency
Direct beach front	Weekly
1km radius	Monthly
10km radius	Quarterly



Aluminium Shutters

- Wipe down shutters using a soft cloth and warm soapy water
- Remove salt residue, stains caused by trees and other marks
- Once clean and dry, spray a light film of silicone spray on hinges or other operational mechanisms
- Shutters located close to the coast need to be washed down weekly



www.advantageblinds.com.au

Bundaberg - 07 4153 3322

Hervey Bay - 07 4124 5666

Gladstone - 07 4972 7270

Brisbane - 07 3299 2499

Rockhampton - 0417 643 517